




影像随心 思锐随行

使用说明

3T系列三脚架套装



广东思锐光学股份有限公司

地址：广东省中山市五桂山第三工业区

电话：0760-89897373 传真：0760-89207062 服务热线：400 830 2299

邮箱：info@sirui-photo.com

网址：www.sirui.com

邮编：529458

3T系列三脚架规格参数

型号	节数	最大直径 mm	最小直径 mm	最小高度 mm	不升中轴高 mm	最大高度 mm	折箱高度 mm	自身重量 kg	最大负重 kg
3T-35K	2	16	13	51	257(含云台) 187(不含云台)	342(含云台) 272(不含云台)	230(含云台) 160(不含云台)	0.39(含云台) 0.22(不含云台)	4
3T-35B	2	16	13	51	257(含云台) 187(不含云台)	342(含云台) 272(不含云台)	230(含云台) 160(不含云台)	0.39(含云台) 0.22(不含云台)	4
3T-35R	2	16	13	51	257(含云台) 187(不含云台)	342(含云台) 272(不含云台)	230(含云台) 160(不含云台)	0.39(含云台) 0.22(不含云台)	4

图纸名称：思锐3T系列说明书

物料编号：PT165-1

制图：彭少章

审核：

批准：

1. 基本结构

2. 中轴伸缩调节

3. 云台及中轴安装操作

4. 微距拍摄

5. 远拍及自拍使用

6. 脚架折叠及展开

7. 短中轴使用

1. 基本结构

2. 中轴升降调节

- ① 逆时针方向旋转a处中轴锁紧圈即可以上下调节中轴高度。
- ② 调节到所需高度位置将a处中轴锁紧圈顺时针方向向旋紧即可固定中轴位置。

3. 云台及中轴安装操作

- ① 中轴拆装：用2.5mm内六角板手逆时针方向旋转或顺时针方向旋转a处中轴紧固螺丝后，再逆时针方向向旋松或顺时针方向向旋紧b处中轴，即可拆下或装上中轴组件。
- ② 云台拆装：顺时针方向向旋紧d处云台底座锁紧螺丝后，用2.5mm内六角板手逆时针方向向旋松或顺时针方向向旋紧e处紧固螺丝后，再逆时针方向向旋松或顺时针方向向旋紧云台e处，即可拆下或装上云台组件。
- ③ 转接平台拆装：用2.5mm内六角板手逆时针方向向旋松或顺时针方向向旋紧f处转接平台紧固螺丝后，再逆时针方向向旋松或顺时针方向向旋紧c处转接平台及螺丝，即可拆下或装上转接平台，也可用此方法调换1/4"、3/8"螺丝。
- ④ 云台快装板拆装：逆时针方向向旋松h处快装板夹座锁紧旋钮，将快装板夹座退至合适距离，按i方向指示斜向取出快装板即可完成拆卸。安装时逆时针方向向旋松h处快装板夹座锁紧旋钮，然后把快装板从夹座侧面推

入井顺时针旋紧h处夹座锁紧旋钮即可完成安装。

4. 微距拍摄

拆卸中轴组件后可按图示接上云台，便可以进行多方位微距拍摄。

5. 远拍及自拍使用

按图示将三个脚片下折到底并将中轴延伸到最长状态，脚架可实现自拍及远距离拍摄功能。

6. 脚架折叠及展开

手持中轴b处，另一手先将三个脚片向下折压使它们与主体旋钮分离后，再逆时针方向向旋紧a处主体旋钮听到“嗒”响声后表示主体旋钮已旋转到位，这时可以把脚片向上折起向最小尺寸以方便携带，展开时按折叠方法逆时针即可。

7. 短中轴使用

本产品配备有一根短中轴，使用短中轴时产品不带云台收折高度仅为130mm，带云台收折高度仅为200mm（带快装板），使用短中轴可使产品收折高度降低，携带更加轻便。

注意：为防止挂钩移动发出响声，在使用3T-35拍摄前请先拆下挂钩。

注意事项：

- 不要超过最大的制定负重（请参考个别产品说明）。
- 当使用产品时，时常紧锁其安全装置。
- 切勿在温度低于零下40摄氏度及高于100摄氏度使用。当在潮湿/沙地/布满尘埃的环境下使用后，谨记将产品弄干及清洁，不建议在海水中使用。
- 切勿将产品长时间放在太阳下曝晒及避免高温环境，例如长时间放在车厢内或玻璃后。
- 在公众地方使用时，如在没有人照料下，切勿留下设备而引致其他公众不便。
- 建议在运输过程中，将设备（例如相机）从脚架上移除。使脚架保持清洁及柔软毛巾清洁，将尘埃及沙粒从所有锁制及活动部件清除。
- 除非有需要，此设备无需定期添加润滑油，如确实需要时，请使用标准润滑油或油蜡。
- 为自身安全着想，切勿将产品接触任何电源。

温馨提醒

请在使用本产品前锁紧以下螺丝
 转接平台紧固螺丝：防止云台在水平转动时转接平台松动
 云台紧固螺丝：防止云台在水平转动时云台松动
 中轴紧固螺丝：防止在锁紧或打开主体旋钮时中轴松动

思锐公司保留对产品升级或变更更多数量的权利，请以实物为准，恕不另行通知。印刷品上如有印刷错误或漏印，敬请谅解。

保修卡

尊敬的顾客：
 感谢您购买思锐的产品！在正常使用过程中，如果因器材本身的材料及工艺出现质量问题，思锐将会提供免费的保修服务。在需要保修服务时，请提供本保修卡和购买凭证（收据或发票，须有商家盖章），思锐公司售后服务热线：400 830 2299

产品名称	保修期限
脚架	6年
云台	3年
防潮拒本体	
电子部分	

产品型号：_____ 购买日期：_____

商店名称：_____ 商店电话：_____

商店地址：_____

商店盖章：_____

顾客须知：

- ① 思锐产品，享受3年免费保修（电子部分为1年），保修时间从购买之日起。
- ② 所修产品，必须是思锐正式授权的经销商或电子商务旗舰店。
- ③ 寄回思锐工厂维修的，请在拨打维修服务热线，待确认故障后，思锐公司承担来回运费。维修期间可在7个工作日内完成维修并寄回。
- ④ 维修前的保修：请先确定发生故障的部件，把该部件卸下单独寄回思锐工厂维修即可，具体可参照使用说明书或致电服务热线。
- ⑤ 以下情况不在保修范围：
 - ① 超过保修期限的；
 - ② 在非思锐正式授权经销商处购买的；
 - ③ 在未授权经销商处代理或维修中心维修过的；
 - ④ 由于不正当操作、意外事件、自然灾害导致的故障或损坏。

*本保修卡只限在中轴大轴使用

维修登记表A

用户姓名	用户电话	用户地址	邮编	故障维修描述	维修人员签名	维修时间

维修登记表B

用户姓名	用户电话	用户地址	邮编	故障维修描述	维修人员签名	维修时间



Professional Photographic Equipment

INSTRUCTIONS

3T Series Tripod Kit



Guangdong SIRUI Optical Co., Ltd.
Address: The Third Industrial District, Wujishan Town, Zhongshan City, Guangdong, China
Tel: 0086-760-89897373 Fax: 0086-760-89207092 Service Hotline: 0086-400-8302299
E-mail: info@sirui-photo.com http://www.sirui.com P.C: 529456

3T Series Tripod Kit Data Chart

Section	Max Dia mm/inch	Min Dia mm/inch	Min Hgt mm/inch	Max Hgt mm/inch	Max Hext mm/inch	Folded H mm/inch	Weight kg/lb	Load kg/lb	
3T-35K	2	16/0.6	13/0.5	51/2.0	257/10.1	342/13.5	230/9.1	0.39/0.86	4/8.8
					(with ball head)	(with ball head)	(with ball head)	(with ball head)	
3T-35B	2	16/0.6	13/0.5	51/2.0	257/10.1	342/13.5	230/9.1	0.39/0.86	4/8.8
					(with ball head)	(with ball head)	(with ball head)	(with ball head)	
3T-35R	2	16/0.6	13/0.5	51/2.0	257/10.1	342/13.5	230/9.1	0.39/0.86	4/8.8
					(with ball head)	(with ball head)	(with ball head)	(with ball head)	

图纸名称：思锐3T系列说明书


物料编号：PT165-1

制图：彭少章


审核：

批准：


1. Know your tripod Kit




2. Center Column Extending and Closing



3. Ball Head and Center Column Operation



4. Macro shooting



1. Know your Tripod

- As shown in Fig 2, turn the Center Column Locking Knob "r" in a counter-clockwise direction, then you can adjust the center column height.
- When you reach the desired height, turn Center Column Locking Knob "r" in a clockwise direction to lock the center column.

2.Center column height adjustment

- As shown in Fig 2, turn the Center Column Locking Knob "r" in a counter-clockwise direction, then you can adjust the center column height.
- When you reach the desired height, turn Center Column Locking Knob "r" in a clockwise direction to lock the center column.

3.Ball head and center column operation

- Remove/replace the Center Column/Short Center Column: Loosen the Center Column by turning the Center Column Locking screw in a counter-clockwise direction with the Allen Key. Unscrew the Center column by turning in a counter-clockwise direction. To replace, place the center column on the 3/8" screw and turn clockwise until tight. Tighten the Center Column Locking screw by turning in a clockwise direction with the Allen Key. Do not force or over-tighten.
- Removing/replacing the ball head: Turn Ball Head Locking Knob "r" in a clockwise direction to lock the ball head and base. Use the Allen key to loosen the Ball Head Locking screw "g", turn the ball head in a counter-clockwise direction to remove it from the platform. To replace, turn the ball head in a clockwise direction, tighten screw "g" by turning Allen key in a clockwise direction. Do not force or over-tighten.


- Removing/attaching Mounting Platform: Use the Allen key to loosen the Mounting Platform Locking Screw "f" (turn counter-clockwise), turn the Mounting Platform and screw counter-clockwise and remove the Mounting Platform. To attach, turn the Mounting Platform and screw in a clockwise direction, until tight, and use the Allen key to tighten the Mounting Platform Locking screw. Do not force or over-tighten. Use the same method to reverse the 1/4" and 3/8" screw.
- Removal/attach QR Plate: turn the QR Clamp Locking Knob "r" in a counter-clockwise direction to loosen the QR Clamp. When the QR Clamp is fully open, remove

7. Using the Short Center Column


The tripod with Short Center Column, folds down to 130mm without the ball head and 200mm with ball head and quick release plate attached. The Short Center Column lets the 3T-35 tripod fold shorter than the telescoping center column - making it easy to carry and light for travel.

Note: To prevent noise caused by the movement of the Ball Hook while shooting videos, you should remove the Ball Hook from the 3T-35.


5. Increased reach/ self-portraits/ remote video



6. Opening and Closing the Tripod



7. Using the Short Center Column



Attention:

- Do not exceed the recommended load limit of the head and/or tripod. (Please refer to product specifications.)
- Please make sure that the locks are securely tightened when in use.
- This product should not be used in environments that exceed the following conditions: (40 ~ +100°C/40 ~ +212°F). And, when used in damp, dirty or dusty environments, please clean and dry thoroughly after use, to assure proper functioning in the future. It is not recommended to expose this product to saltwater. If exposed, please clean with mild soap and warm water and towel dry.
- Please keep from high temperatures and direct exposure to bright sunlight for extended periods of time.
- Please do not leave the equipment alone in a public place, which can be an inconvenience or hazard to others.
- To protect your camera gear, please remove it from the tripod/ball head when transporting from place to place.
- Please use a soft towel with warm water and mild soap to clean the locking system and gliding parts when necessary. Towel dry before storing the tripod.
- Under most situations, there is no need to lubricate any parts of this product. The addition of most lubricants will gum up the mechanisms and reduce their normal gliding characteristics. Please call or email us if you have any questions or special needs.
- Please keep this product away from all electrical power sources.

CAUTION

Please tighten the below before using the tripod.
Mounting Platform Locking screw to prevent the Mounting Platform from loosening while panning the ball head.
Ball Head Locking screw to prevent the ball head from loosening while panning.
Center Column Locking screw to prevent the center column from loosening when locking/unlocking the tripod legs.

Specifications are subject to change without notice.

WARRANTY CARD INFORMATION

Dear SIRUI Customer,
Thank you for your purchase of SIRUI Professional Products!
SIRUI warrants that your purchase is free from defects in materials and workmanship under normal use during the Limited Warranty Period. The Warranty begins on the original date of purchase on your sales receipt, and is not transferable. If service is required, a copy of the sales receipt must be included with an explanation of the problem.

Product	Warranty Length
Tripods / Monopods / Accessories	6 years
Humidity Control Cabinet (Cabinet)	3 years

Model: _____ Date: _____
Serial Number: _____

Warranty coverage can differ from region. Please see the contact information below for product registration, information and service for the region the product was purchased in.

SIRUI 6 (Six) Year Limited Warranty (3 Year Warranty for Electronic Parts). This warranty shall be limited to repair, adjustment and/or replacement at SIRUI or its authorized distributors option, of defective parts, free of charge (except the cost of transportation to the distributor/service center). Responsibility is limited to the actual cost of the item. Call or Email with questions and service before sending any product to the center in your region. Below is a listing of contact information for Product Registration, Service Inquiries and Questions. SIRUI will not be responsible for expenses or inconveniences, or consequential damages to equipment, or by breach of any expressed or implied warranties.

Limitations:
This warranty is not transferable.
This warranty covers all defects encountered in normal use of the equipment and does not apply in the following cases:
1. If the equipment has been serviced by other than an authorized SIRUI Service Center.
2. Damage to the equipment is due to modification (including but not limited to, unauthorized use, misuse, accident, fire, lightning, water damage, etc.) or not following operating instructions.
3. No valid proof of purchase is provided.
4. Damage caused by acts of nature (including, but not limited to: fires, floods or earthquakes).
*W-Series Waterproof/Dustproof models - Warranty coverage can differ from region to region. Please see contact information below for product registration, information and service for the region the product was purchased in.

Warranty Address and Contact Information:

(Please contact the seller or the local distributor where the product was purchased for warranty issues or questions and before any product is sent.)

1. Guangdong SIRUI Optical Co., Ltd.

The Third Industrial District, Wujishan Town, Zhongshan City, Guangdong, China
Tel: 0086-760-89897373 Fax: 0086-760-89207092
Service Hotline: 0086-400-830-2299
E-mail: info@sirui-photo.com
http://www.sirui-photo.com

2. SIRUI USA, LLC

Add: 29 Commerce Court, Verona, NJ 07044
www.sirui.com
Service Toll Free 866-373-0829 E-mail: info@sirui.com
FOR PRODUCTS PURCHASED IN THE USA PLEASE SEE:
For full details on our USA Warranty Terms and Limitations:
www.sirui.com/warranty.html
to register products: www.sirui.com/product-registration.html

3. Focus Nordic AB

For technical support, service or repairs, please contact:
Sweden: info@focusnordic.se www.focusnordic.se
Denmark: info@focusnordic.dk www.focusnordic.dk
Finland: info@focusnordic.fi www.focusnordic.fi
Iceland: info@focusnordic.is www.focusnordic.is
Latvia: info@focusnordic.lv www.focusnordic.lv
Estonia: info@focusnordic.ee www.focusnordic.ee
Lithuania: info@focusnordic.lt www.focusnordic.lt
Poland: info@focusnordic.pl www.focusnordic.pl

4. SIRUI Europe GmbH (European Service Center)

Add: Federatastr. 2, 14059 Berlin, Germany
Phone: +49 221 94 99 54-50 E-mail: info@sirui.de
Please contact the seller or your local distributor for warranty issues.)
5. TSE Imaging BV
Add: Argonneweg 135, 1362AD Almere, The Netherlands
Telephone: +31 (0)36 5450348 E-mail: service@tse-imaging.nl
(Exclusive Distributor for Netherlands, Belgium, Luxembourg)
www.sirui-photo.nl

6. 디에스티에프라이프

한국 총판: 기흥구 가림동 비즈서비스센터
서울특별시 중구 남대문로 10, 1층
Tel: 02-752-3304 Fax: 02-74-9903
www.sirui.co.kr lowepiok@gmail.com